


Features

- Peak pulse power:
 - 600 W (10/1000 µs)
 - 4 kW (8/20 µs)
- Stand off voltage range: from 5 V to 188 V
- Unidirectional and bidirectional types
- Low leakage current:
 - 0.2 µA at 25 °C
 - 1 µA at 85 °C
- Operating T_j max: 150 °C
- High power capability at T_j max:
 - 515 W (10/1000 µs)
- JEDEC registered package outline

Complies with the following standards

- IEC 61000-4-2 level 4:
 - 15 kV (air discharge)
 - 8 kV (contact discharge)
- IEC 61000-4-5
- MIL STD 883G, method 3015-7 Class 3B:
 - 25 kV HBM (human body model)
- Resin meets UL 94, V0
- MIL-STD-750, method 2026 soldererability
- EIA STD RS-481 and IEC 60286-3 packing
- IPC 7531 footprint



Description

The SMBJ Transil series has been designed to protect sensitive equipment against electrostatic discharges according to IEC 61000-4-2, and MIL STD 883, method 3015, and electrical over stress according to IEC 61000-4-4 and 5. These devices are more generally used against surges below 600 W (10/1000 µs).

Planar technology makes these devices suitable for high-end equipment and SMPS where low leakage current and high junction temperature are required to provide reliability and stability over time.

SMBJ are packaged in SMB (SMB footprint in accordance with IPC 7531 standard).

TM: Transil is a trademark of STMicroelectronics

1 Characteristics

Table 1. Absolute maximum ratings ($T_{amb} = 25^{\circ}\text{C}$)

| Symbol | Parameter | Value | Unit |
|-----------|--|-------------|--------------------|
| P_{PP} | Peak pulse power dissipation ⁽¹⁾ T_j initial = T_{amb} | 600 | W |
| T_{stg} | Storage temperature range | -65 to +150 | $^{\circ}\text{C}$ |
| T_j | Operating junction temperature range | -55 to +150 | $^{\circ}\text{C}$ |
| T_L | Maximum lead temperature for soldering during 10 s. | 260 | $^{\circ}\text{C}$ |

1. For a surge greater than the maximum values, the diode will fail in short-circuit.

Table 2. Thermal resistances

| Symbol | Parameter | Value | Unit |
|---------------|---|-------|----------------------|
| $R_{th(j-l)}$ | Junction to leads | 20 | $^{\circ}\text{C/W}$ |
| $R_{th(j-a)}$ | Junction to ambient on recommended pad layout | 100 | $^{\circ}\text{C/W}$ |

Figure 1. Electrical characteristics - definitions




Figure 2. Pulse definition for electrical characteristics




Table 3. Electrical characteristics - parameter values ($T_{amb} = 25^{\circ}\text{C}$)

| Order code | I _{RM} max@V _{RM} | | | V _{BR} @ I _R ⁽¹⁾ | | | V _{CL} @ I _{PP} 10/1000 μs | | R _D ⁽²⁾ 10/1000 μs | | V _{CL} @ I _{PP} 8/20 μs | | R _D ⁽²⁾ 8/20 μs | | αT ⁽³⁾ |
|-------------|-------------------------------------|-------|-----|---|------|----|---|------|---|------|--|-------|--|----------|-------------------|
| | 25 °C | 85 °C | | min | typ | | max | | | max | | | | max | |
| | μA | V | V | | mA | V | A ⁽⁴⁾ | | Ω | V | A ⁽⁴⁾ | | Ω | 10-4/ °C | |
| SMBJ5.0A/CA | 20 | 50 | 5.0 | 6.4 | 6.74 | 10 | 9.2 | 68 | 0.031 | 13.4 | 298 | 0.021 | 5.7 | | |
| SMBJ6.0A/CA | 20 | 50 | 6.0 | 6.7 | 7.05 | 10 | 10.3 | 61 | 0.048 | 13.7 | 290 | 0.022 | 5.9 | | |
| SMBJ6.5A/CA | 20 | 50 | 6.5 | 7.2 | 7.58 | 10 | 11.2 | 56 | 0.058 | 14.5 | 276 | 0.024 | 6.1 | | |
| SMBJ8.5A/CA | 20 | 50 | 8.5 | 9.4 | 9.9 | 1 | 14.4 | 41.7 | 0.096 | 19.5 | 205 | 0.044 | 7.3 | | |
| SMBJ10A/CA | 0.2 | 1 | 10 | 11.1 | 11.7 | 1 | 17 | 37 | 0.127 | 21.7 | 184 | 0.051 | 7.8 | | |
| SMBJ12A/CA | 0.2 | 1 | 12 | 13.3 | 14 | 1 | 19.9 | 31 | 0.168 | 25.3 | 157 | 0.068 | 8.3 | | |
| SMBJ13A/CA | 0.2 | 1 | 13 | 14.4 | 15.2 | 1 | 21.5 | 29 | 0.191 | 27.2 | 147 | 0.076 | 8.4 | | |
| SMBJ15A/CA | 0.2 | 1 | 15 | 16.7 | 17.6 | 1 | 24.4 | 25.1 | 0.236 | 32.5 | 123 | 0.114 | 8.8 | | |
| SMBJ16A/CA | 0.2 | 1 | 16 | 17.8 | 18.7 | 1 | 26 | 23.1 | 0.276 | 34.4 | 116 | 0.127 | 8.8 | | |
| SMBJ18A/CA | 0.2 | 1 | 18 | 20.0 | 21.1 | 1 | 29.2 | 21.5 | 0.328 | 39.3 | 102 | 0.168 | 9.2 | | |
| SMBJ20A/CA | 0.2 | 1 | 20 | 22.2 | 23.4 | 1 | 32.4 | 19.4 | 0.404 | 42.8 | 93 | 0.196 | 9.4 | | |
| SMBJ22A/CA | 0.2 | 1 | 22 | 24.4 | 25.7 | 1 | 35.5 | 17.7 | 0.481 | 48.3 | 83 | 0.257 | 9.6 | | |
| SMBJ24A/CA | 0.2 | 1 | 24 | 26.7 | 28.1 | 1 | 38.9 | 16 | 0.587 | 50 | 80 | 0.256 | 9.6 | | |
| SMBJ26A/CA | 0.2 | 1 | 26 | 28.9 | 30.4 | 1 | 42.1 | 14.9 | 0.683 | 53.5 | 75 | 0.288 | 9.7 | | |
| SMBJ28A/CA | 0.2 | 1 | 28 | 31.1 | 32.7 | 1 | 45.4 | 13.8 | 0.802 | 59 | 68 | 0.363 | 9.8 | | |
| SMBJ30A/CA | 0.2 | 1 | 30 | 33.3 | 35.1 | 1 | 48.4 | 13 | 0.888 | 64.3 | 62 | 0.443 | 9.9 | | |
| SMBJ33A/CA | 0.2 | 1 | 33 | 36.7 | 38.6 | 1 | 53.3 | 11.8 | 1.08 | 69.7 | 57 | 0.512 | 10.0 | | |
| SMBJ36A/CA | 0.2 | 1 | 36 | 40.0 | 42.1 | 1 | 58.1 | 10.3 | 1.35 | 76 | 52 | 0.611 | 10.0 | | |
| SMBJ40A/CA | 0.2 | 1 | 40 | 44.4 | 46.7 | 1 | 64.5 | 9.7 | 1.59 | 84 | 48 | 0.728 | 10.1 | | |
| SMBJ48A/CA | 0.2 | 1 | 48 | 53.3 | 56.1 | 1 | 77.4 | 8.1 | 2.28 | 100 | 40 | 1.03 | 10.3 | | |
| SMBJ58A/CA | 0.2 | 1 | 58 | 64.4 | 67.8 | 1 | 93.6 | 6.7 | 3.34 | 121 | 33 | 1.51 | 10.4 | | |
| SMBJ70A/CA | 0.2 | 1 | 70 | 77.8 | 81.9 | 1 | 113 | 5.5 | 4.91 | 146 | 27 | 2.22 | 10.5 | | |
| SMBJ85A/CA | 0.2 | 1 | 85 | 94 | 99 | 1 | 137 | 4.6 | 7.18 | 178 | 22.5 | 3.29 | 10.6 | | |
| SMBJ100A/CA | 0.2 | 1 | 100 | 111 | 117 | 1 | 162 | 3.8 | 10.3 | 212 | 19 | 4.69 | 10.7 | | |
| SMBJ130A/CA | 0.2 | 1 | 130 | 144 | 152 | 1 | 209 | 3 | 16.5 | 265 | 15 | 7.03 | 10.8 | | |
| SMBJ154A/CA | 0.2 | 1 | 154 | 171 | 180 | 1 | 246 | 2.4 | 23.8 | 317 | 12.6 | 10.2 | 10.8 | | |
| SMBJ170A/CA | 0.2 | 1 | 170 | 189 | 199 | 1 | 275 | 2.2 | 30.0 | 353 | 11.3 | 12.7 | 10.8 | | |
| SMBJ188A/CA | 0.2 | 1 | 188 | 209 | 220 | 1 | 328 | 2 | 48.5 | 388 | 10.3 | 15.2 | 10.8 | | |

1. Pulse test : t_p < 50 ms
2. To calculate maximum clamping voltage at other surge level, use the following formula: V_{CLmax} = V_{CL} - R_D × (I_{PP} - I_{PPappli}) where I_{PPappli} is the surge current in the application
3. To calculate V_{BR} or V_{CL} versus junction temperature, use the following formulas:
 $V_{BR} @ T_J = V_{BR} @ 25^{\circ}\text{C} \times (1 + \alpha T \times (T_J - 25))$
 $V_{CL} @ T_J = V_{CL} @ 25^{\circ}\text{C} \times (1 + \alpha T \times (T_J - 25))$
4. Surge capability given for both directions for unidirectional and bidirectional types.

Figure 3. Peak pulse power dissipation versus initial junction temperature




Figure 4. Peak pulse power versus exponential pulse duration (T_j initial = 25 °C)




Figure 5. Clamping voltage versus peak pulse current (exponential waveform, maximum values)




Figure 6. Junction capacitance versus reverse applied voltage for unidirectional types (typical values)




Figure 8. Peak forward voltage drop versus peak forward current (typical values)




Figure 10. Thermal resistance, junction to ambient, versus copper surface under each lead




Figure 7. Junction capacitance versus reverse applied voltage for bidirectional types (typical values)




Figure 9. Relative variation of thermal impedance, junction to ambient, versus pulse duration






Figure 11. Leakage current versus junction temperature (typical values)



2 Ordering information scheme

Figure 12. Ordering information scheme




3 Package information

- Case: JEDEC DO-214AA molded plastic over planar junction
- Terminals: solder plated - solderable per MIL-STD-750, Method 2026
- Polarity: for unidirectional types the band indicates cathode
- Flammability: epoxy is rated UL94V-0
- RoHS package

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.


Table 4. SMB dimensions

| Ref. | Dimensions | | | |
|------|-------------|------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A1 | 1.90 | 2.45 | 0.075 | 0.096 |
| A2 | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 1.95 | 2.20 | 0.077 | 0.087 |
| c | 0.15 | 0.40 | 0.006 | 0.016 |
| D | 3.30 | 3.95 | 0.130 | 0.156 |
| E | 5.10 | 5.60 | 0.201 | 0.220 |
| E1 | 4.05 | 4.60 | 0.159 | 0.181 |
| L | 0.75 | 1.50 | 0.030 | 0.059 |



**Figure 13. Footprint dimensions
in mm (inches)**

Figure 14. Marking layout⁽¹⁾



1. Marking layout can vary according to assembly location.

Table 5. Marking

| Order code | Marking | Order code | Marking |
|-------------|---------|--------------|---------|
| SMBJ5.0A-TR | BUZ | SMBJ5.0CA-TR | BBZ |
| SMBJ6.0A-TR | BUA | SMBJ6.0CA-TR | BBA |
| SMBJ6.5A-TR | BUB | SMBJ6.5CA-TR | BBB |
| SMBJ8.5A-TR | BUC | SMBJ8.5CA-TR | BBC |
| SMBJ10A-TR | BUD | SMBJ10CA-TR | BBD |
| SMBJ12A-TR | BUE | SMBJ12CA-TR | BBE |
| SMBJ13A-TR | BUF | SMBJ13CA-TR | BBF |
| SMBJ15A-TR | BUG | SMBJ15CA-TR | BBG |
| SMBJ16A-TR | CUG | SMBJ16CA-TR | CBG |
| SMBJ18A-TR | BUH | SMBJ18CA-TR | BBH |
| SMBJ20A-TR | BUI | SMBJ20CA-TR | BBI |
| SMBJ22A-TR | BVA | SMBJ22CA-TR | CBH |
| SMBJ24A-TR | BUJ | SMBJ24CA-TR | BBJ |
| SMBJ26A-TR | BUK | SMBJ26CA-TR | BBK |
| SMBJ28A-TR | BUL | SMBJ28CA-TR | BBL |
| SMBJ30A-TR | BUM | SMBJ30CA-TR | BBM |
| SMBJ33A-TR | BUN | SMBJ33CA-TR | BBN |
| SMBJ36A-TR | CUN | SMBJ36CA-TR | CBN |
| SMBJ40A-TR | CUJ | SMBJ40CA-TR | CBJ |
| SMBJ43A-TR | CUW | SMBJ43CA-TR | CBW |
| SMBJ48A-TR | BUW | SMBJ48CA-TR | BBW |
| SMBJ58A-TR | BUO | SMBJ58CA-TR | BBO |
| SMBJ70A-TR | CUM | SMBJ70CA-TR | CBM |
| SMBJ85A-TR | BUQ | SMBJ85CA-TR | BBQ |
| SMBJ100A-TR | CUQ | SMBJ100CA-TR | CBQ |
| SMBJ130A-TR | BUS | SMBJ130CA-TR | BBS |
| SMBJ154A-TR | BUT | SMBJ154CA-TR | BBT |
| SMBJ170A-TR | BUU | SMBJ170CA-TR | BBU |
| SMBJ188A-TR | BUV | SMBJ188CA-TR | BBV |

4 Ordering information

Table 6. Order codes

| Order code | Marking | Package | Weight | Base qty | Delivery mode |
|-------------------------------|---------------------------------------|---------|--------|----------|---------------|
| SMBJxxxA/CA-TR ⁽¹⁾ | See Table 5 on page 8 | SMB | 0.11 g | 2500 | Tape and reel |

1. Where xxx is nominal value of V_{BR} and A or CA indicates unidirectional or bidirectional version. See [Table 3](#) for list of available devices and their order codes

5 Revision history

Table 7. Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| Oct-2001 | 4 | Previous issue |
| 10-Feb-2005 | 5 | Reformatted to current template. Added directional (uni and bi) indications to graphics. Added ECOPACK statement. |
| 16-Nov-2006 | 6 | Add part numbers SMBJ36A-TR and SMBJ36CA-TR in Table 3 . |
| 14-May-2009 | 7 | Reformatted to current standards. Updated ECOPACK statement. Added part number SMBJ43CA/A |
| 17-Sep-2009 | 8 | Document updated for low leakage current. |
| 09-Jul-2010 | 9 | Changed timescale in Figure 9 . |
| 20-Oct-2010 | 10 | Updated Figure 13 . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2010 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com