


## Reflective Optical Sensor with Transistor Output



### FEATURES

- Package type: leaded
- Detector type: phototransistor
- Dimensions (L x W x H in mm): 10.2 x 5.8 x 7
- Peak operating distance: 2.5 mm
- Operating range within > 20 % relative collector current: 0.2 mm to 15 mm
- Typical output current under test:  $I_C = 1$  mA
- Daylight blocking filter
- Emitter wavelength: 950 nm
- Lead (Pb)-free soldering released
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### DESCRIPTION

The TCRT5000 and TCRT5000L are reflective sensors which include an infrared emitter and phototransistor in a leaded package which blocks visible light. The package includes two mounting clips. TCRT5000L is the long lead version.

### APPLICATIONS

- Position sensor for shaft encoder
- Detection of reflective material such as paper, IBM cards, magnetic tapes etc.
- Limit switch for mechanical motions in VCR
- General purpose - wherever the space is limited

### PRODUCT SUMMARY

| PART NUMBER | DISTANCE FOR MAXIMUM CTR <sub>rel</sub> <sup>(1)</sup> (mm) | DISTANCE RANGE FOR RELATIVE $I_{out} > 20\%$ (mm) | TYPICAL OUTPUT CURRENT UNDER TEST <sup>(2)</sup> (mA) | DAYLIGHT BLOCKING FILTER INTEGRATED |
|-------------|-------------------------------------------------------------|---------------------------------------------------|-------------------------------------------------------|-------------------------------------|
| TCRT5000    | 2.5                                                         | 0.2 to 15                                         | 1                                                     | Yes                                 |
| TCRT5000L   | 2.5                                                         | 0.2 to 15                                         | 1                                                     | Yes                                 |

#### Notes

<sup>(1)</sup> CTR: current transference ratio,  $I_{out}/I_{in}$

<sup>(2)</sup> Conditions like in table basic characteristics/sensors

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING | VOLUME <sup>(1)</sup>      | REMARKS            |
|---------------|-----------|----------------------------|--------------------|
| TCRT5000      | Tube      | MOQ: 4500 pcs, 50 pcs/tube | 3.5 mm lead length |
| TCRT5000L     | Tube      | MOQ: 2400 pcs, 48 pcs/tube | 15 mm lead length  |

#### Note

<sup>(1)</sup> MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>

| PARAMETER              | TEST CONDITION            | SYMBOL    | VALUE | UNIT       |
|------------------------|---------------------------|-----------|-------|------------|
| <b>INPUT (EMITTER)</b> |                           |           |       |            |
| Reverse voltage        |                           | $V_R$     | 5     | V          |
| Forward current        |                           | $I_F$     | 60    | mA         |
| Forward surge current  | $t_p \leq 10 \mu s$       | $I_{FSM}$ | 3     | A          |
| Power dissipation      | $T_{amb} \leq 25^\circ C$ | $P_V$     | 100   | mW         |
| Junction temperature   |                           | $T_j$     | 100   | $^\circ C$ |

## ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>

| PARAMETER                 | TEST CONDITION                  | SYMBOL    | VALUE         | UNIT             |
|---------------------------|---------------------------------|-----------|---------------|------------------|
| <b>OUTPUT (DETECTOR)</b>  |                                 |           |               |                  |
| Collector emitter voltage |                                 | $V_{CEO}$ | 70            | V                |
| Emitter collector voltage |                                 | $V_{ECO}$ | 5             | V                |
| Collector current         |                                 | $I_C$     | 100           | mA               |
| Power dissipation         | $T_{amb} \leq 55^\circ\text{C}$ | $P_V$     | 100           | mW               |
| Junction temperature      |                                 | $T_j$     | 100           | $^\circ\text{C}$ |
| <b>SENSOR</b>             |                                 |           |               |                  |
| Total power dissipation   | $T_{amb} \leq 25^\circ\text{C}$ | $P_{tot}$ | 200           | mW               |
| Ambient temperature range |                                 | $T_{amb}$ | - 25 to + 85  | $^\circ\text{C}$ |
| Storage temperature range |                                 | $T_{stg}$ | - 25 to + 100 | $^\circ\text{C}$ |
| Soldering temperature     | 2 mm from case, $t \leq 10$ s   | $T_{sd}$  | 260           | $^\circ\text{C}$ |

### Note

<sup>(1)</sup>  $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

## ABSOLUTE MAXIMUM RATINGS




Fig. 1 - Power Dissipation Limit vs. Ambient Temperature

## BASIC CHARACTERISTICS <sup>(1)</sup>

| PARAMETER                            | TEST CONDITION                             | SYMBOL               | MIN. | TYP. | MAX. | UNIT  |
|--------------------------------------|--------------------------------------------|----------------------|------|------|------|-------|
| <b>INPUT (EMITTER)</b>               |                                            |                      |      |      |      |       |
| Forward voltage                      | $I_F = 60$ mA                              | $V_F$                |      | 1.25 | 1.5  | V     |
| Junction capacitance                 | $V_R = 0$ V, $f = 1$ MHz                   | $C_j$                |      | 17   |      | pF    |
| Radiant intensity                    | $I_F = 60$ mA, $t_p = 20$ ms               | $I_e$                |      |      | 21   | mW/sr |
| Peak wavelength                      | $I_F = 100$ mA                             | $\lambda_P$          | 940  |      |      | nm    |
| Virtual source diameter              | Method: 63 % encircled energy              | $d$                  |      | 2.1  |      | mm    |
| <b>OUTPUT (DETECTOR)</b>             |                                            |                      |      |      |      |       |
| Collector emitter voltage            | $I_C = 1$ mA                               | $V_{CEO}$            | 70   |      |      | V     |
| Emitter collector voltage            | $I_e = 100$ $\mu\text{A}$                  | $V_{ECO}$            | 7    |      |      | V     |
| Collector dark current               | $V_{CE} = 20$ V, $I_F = 0$ A, $E = 0$ lx   | $I_{CEO}$            |      | 10   | 200  | nA    |
| <b>SENSOR</b>                        |                                            |                      |      |      |      |       |
| Collector current                    | $V_{CE} = 5$ V, $I_F = 10$ mA, $D = 12$ mm | $I_C^{(2)(3)}$       | 0.5  | 1    | 2.1  | mA    |
| Collector emitter saturation voltage | $I_F = 10$ mA, $I_C = 0.1$ mA, $D = 12$ mm | $V_{CEsat}^{(2)(3)}$ |      |      | 0.4  | V     |

### Note

<sup>(1)</sup>  $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

<sup>(2)</sup> See figure 3

<sup>(3)</sup> Test surface: mirror (Mfr. Spindler a. Hoyer, Part No. 340005)




Fig. 2 - Test Circuit




Fig. 3 - Test Circuit

### BASIC CHARACTERISTICS

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified




Fig. 4 - Forward Current vs. Forward Voltage




Fig. 6 - Collector Current vs. Forward Current




Fig. 5 - Relative Current Transfer Ratio vs. Ambient Temperature




Fig. 7 - Collector Emitter Saturation Voltage vs. Collector Current

# TCRT5000, TCRT5000L

Vishay Semiconductors

Reflective Optical Sensor with  
Transistor Output




Fig. 8 - Current Transfer Ratio vs. Forward Current






Fig. 9 - Relative Collector Current vs. Distance

## PACKAGE DIMENSIONS in millimeters, TCRT5000



### PACKAGE DIMENSIONS in millimeters, TCRT5000L




# TCRT5000, TCRT5000L

Vishay Semiconductors


Reflective Optical Sensor with  
Transistor Output



## TUBE DIMENSIONS in millimeters, TCRT5000



## TUBE DIMENSIONS in millimeters, TCRT5000L



## Packaging and Ordering Information


| PART NUMBER   | MOQ <sup>(1)</sup> | PCS PER TUBE | TUBE SPEC. (FIGURE) | CONSTITUENTS (FORMS) |
|---------------|--------------------|--------------|---------------------|----------------------|
| CNY70         | 4000               | 80           | 1                   | 28                   |
| TCPT1300X01   | 2000               | Reel         | (2)                 | 29                   |
| TCRT1000      | 1000               | Bulk         | -                   | 26                   |
| TCRT1010      | 1000               | Bulk         | -                   | 26                   |
| TCRT5000      | 4500               | 50           | 2                   | 27                   |
| TCRT5000L     | 2400               | 48           | 3                   | 27                   |
| TCST1030      | 5200               | 65           | 5                   | 24                   |
| TCST1030L     | 2600               | 65           | 6                   | 24                   |
| TCST1103      | 1020               | 85           | 4                   | 24                   |
| TCST1202      | 1020               | 85           | 4                   | 24                   |
| TCST1230      | 4800               | 60           | 7                   | 24                   |
| TCST1300      | 1020               | 85           | 4                   | 24                   |
| TCST2103      | 1020               | 85           | 4                   | 24                   |
| TCST2202      | 1020               | 85           | 4                   | 24                   |
| TCST2300      | 1020               | 85           | 4                   | 24                   |
| TCST5250      | 4860               | 30           | 8                   | 24                   |
| TCUT1300X01   | 2000               | Reel         | (2)                 | 29                   |
| TCZT8020-PAER | 2500               | Bulk         | -                   | 22                   |

### Notes

(1) MOQ: minimum order quantity

(2) Please refer to datasheets

### TUBE SPECIFICATION FIGURES



With rubber stopper

Tolerance:  $\pm 0.5\text{mm}$

Length:  $575 \pm 1\text{mm}$

Drawing-No.: 9.700-5097.01-4

Issue: 1; 25.02.00

15198

Fig. 1




Fig. 2




Fig. 3






Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.